

Printing date 12.06.2020 Revision: 10.10.2018

### 1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: UltraSeal XT™ plus

· Article number: XA/73401, XB/13560, XR/56303, XT/10952

· Index number: SDS: 25-001.16

· Relevant identified uses of the substance or mixture and uses advised against

Professional Dental Pit and Fissure Sealant

· Application of the substance / the mixture Professional Dental Pit and Fissure Sealant

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Ultradent Products Inc.

505 W. Ultradent Drive (10200 S)

South Jordan, UT 84095-3942

USA

on line order support @ultradent.com

EC Responsible Person
Ultradent Products GmbH
Am Westhover Berg 30
51149 Cologne Germany

Email: infoDE@ultradent.com

Emergency Phone: +49(0)2203-35-92-0

· Further information obtainable from: Customer Service

· Emergency telephone number:

CHEMTREC (NORTH AMERICA) : (800) 424-9300 (INTERNATIONAL) : +(703) 527-3887

### 2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The Regulation EC 1272/2008 on classification, labeling and packaging of substances and mixtures (CLP) shall not apply to a medical device in the finished state used in direct physical contact with the human body according to Art. 1.5 (d). Therefore, the product is exempted from the CLP labeling requirements, and no SDS is required by Regulation 1907/2006, Art. 2 (6c), REACH. Therefore, all given data, classification, and information on this SDS are provided solely on a voluntary basis.

- · Hazard pictograms GHS07
- · Signal word Warning
- · Hazard-determining components of labelling:

Triethylene Glycol Dimethacrylate

Diurethane Dimethacrylate

Organophosphine Oxide

· Hazard statements

H317 May cause an allergic skin reaction.

(Contd. on page 2)

Printing date 12.06.2020 Revision: 10.10.2018

Trade name: UltraSeal XT™ plus

(Contd. of page 1)

#### · Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- *P272* Contaminated work clothing should not be allowed out of the workplace.
- P280 Wear protective gloves.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- *P321* Specific treatment (see on this label).
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 109-16-0	Triethylene Glycol Dimethacrylate	>10-≤25%	
EINECS: 203-652-6	<b>♦</b> Skin Sens. 1, H317		
CAS: 72869-86-4	Diurethane Dimethacrylate	>2.5- <b>≤</b> 10%	
EINECS: 276-957-5	<b>♦</b> Skin Sens. 1, H317		
CAS: 1344-28-1	Aluminium Oxide	>2.5-≤10%	
EINECS: 215-691-6	substance with a Community workplace exposure limit		
CAS: 868-77-9	2-Hydroxyethyl Methacrylate	≤2.5%	
EINECS: 212-782-2	💠 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317		
	Amine Methacrylate	≤2.5%	
	♠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317		
CAS: 162881-26-7	Organophosphine Oxide	≤2.5%	
ELINCS: 423-340-5	💠 Skin Sens. 1, H317; Aquatic Chronic 4, H413		
CAS: 10163-15-2	Sodium Monofluorophosphate	0.1%	
EINECS: 233-433-0	♦ Acute Tox. 4, H302		

<sup>•</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

#### 4 First aid measures

- Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

*In case of unconsciousness place patient stably in side position for transportation.* 

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If swallowed in large quantities seek medical attention.

(Contd. on page 3)

Printing date 12.06.2020 Revision: 10.10.2018

Trade name: UltraSeal XT™ plus

(Contd. of page 2)

- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### 5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Foam, dry chemical, carbon dioxide

Use fire extinguishing methods suitable to surrounding conditions.

- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters:
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling:

Avoid contact with eyes, skin, and clothing. Use suitable protective equipment.

Ensure good ventilation/exhaustion at the workplace.

- · Information about fire and explosion protection: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: See product labeling.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: See product labelling.
- · Specific end use(s) Professional Dental Pit and Fissure Sealant

### 8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

Printing date 12.06.2020 Revision: 10.10.2018

Trade name: UltraSeal XT™ plus

(Contd. of page 3)

#### · Control parameters

· Ingredients with limi	t values that require monitoring at the workplace:
1344-28-1 Aluminiu	m Oxide
WEL (Great Britain)	Long-term value: 10* 4** mg/m³ *inhalable dust **respirable dust
	*inhalable dust **respirable dust
79-41-4 Methacrylic	Acid
WEL (Great Britain)	Short-term value: 143 mg/m³, 40 ppm Long-term value: 72 mg/m³, 20 ppm
	Long-term value: 72 mg/m³, 20 ppm

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

chemical mixture.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Not required.
- · **Body protection:** Protective work clothing

#### 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Colour: Shade dependent

**Odour:** Acrylic

· *Odour threshold:* Not determined.

· pH-value: Not applicable (non-aqueous)

· Change in condition

Melting point/freezing point: Undetermined.

(Contd. on page 5)

Printing date 12.06.2020 Revision: 10.10.2018

Trade name: UltraSeal XT™ plus

		(Contd. of page
Initial boiling point and boiling range	e: Undetermined.	
Flash point:	>100 °C	
Flammability (solid, gas):	Not determined.	
Ignition temperature:	445 °C	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapour pressure at 20 °C:	0 hPa	
Density at 20 °C:	1.7-1.8 g/cm³	
Relative density	Not determined.	
Vapour density	Not applicable.	
Evaporation rate	Not applicable.	
Solubility in / Miscibility with		
water:	Insoluble.	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity:		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
Solvent content:		
Solids content:	<60.0 %	
Other information	No further relevant information available.	

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: Avoid light exposure
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	values relev	ant for classification:
109-16-0	Triethylene (	Glycol Dimethacrylate
Oral	LD50	>5,000 mg/kg (rat)
	LC50 Fish	16.4 mg/l (Fish) (Toxicity to fish)

(Contd. on page 6)

Printing date 12.06.2020 Revision: 10.10.2018

Trade name: UltraSeal XT™ plus

		(Contd. of page 5
Dermal	LD50	>2,000 mg/kg (mouse)
72869-86-	4 Diurethan	ne Dimethacrylate
Oral	LD50	>5,000 mg/kg (rat)
1344-28-1	Aluminium	Oxide
Oral	LD50	>5,000 mg/kg (rat)
79-41-4 M	ethacrylic A	lcid
Oral	LD50	1,250 mg/kg (mouse)
		1,060 mg/kg (rat)
		1,200 mg/kg (rabbit)
	LC50 Fish	86 mg/l (Fish)
Dermal	LD50	1,000 mg/kg (Guinea pig)
		500 mg/kg (rabbit)
Inhalative	LC50/4 h	7.1 mg/l (rat)
162881-26	-7 Organop	hosphine Oxide
Oral	LD50	>2,000 mg/kg (rat)
	LC50 Fish	>0.09 mg/l (Fish) (Toxicity to fish)
Dermal	LD50	>2,000 mg/kg (rat)

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

Toxicity	
Aquatic toxicity:	
109-16-0 Triethylene Gly	col Dimethacrylate
Biodegradability	28 days (Aerobic) (Biodegradability testing)
Aqua toxicity	32 mg/l (daphnia) (No Observed Effect Concentration)
EC50	>100 mg/l (Algae) (Toxicity to algae)
72869-86-4 Diurethane I	Dimethacrylate
Biodegradability	28 days (Aerobic) (Biodegradability testing)
EC50	>0.6 mg/l (Algae) (Toxicity to algae)
	>1.2 mg/l (daphnia) (Toxicity to aquatic invertebrates)
79-41-4 Methacrylic Acid	1
EC50	<180 mg/kg (daphnia) (Toxicity to aquatic invertebrates)
EC50	45 mg/l (Algae) (Toxicity to algae)

(Contd. of page 6)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.06.2020 Revision: 10.10.2018

Trade name: UltraSeal XT™ plus

162881-26-7 Organophosphine Oxide

EC50 (static) >1.175 mg/kg (daphnia) (Toxicity to aquatic invertebrates)

Aqua toxicity ≥0.008 mg/l (daphnia) (Daphnia Magna Reproduction Test)

Toxicity to Aquatic Plants (static) >0.26 mg/l (Plant) (Toxicity to algae)

- Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Europ	pean waste catalogue
HP8	Corrosive
HP13	Sensitising

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

Transport information		
UN-Number ADR, ADN, IMDG, IATA	not regulated	
UN proper shipping name ADR, ADN, IMDG, IATA	not regulated	
Transport hazard class(es)		
ADR, ADN, IMDG, IATA Class	not regulated	
Packing group ADR, IMDG, IATA	not regulated	
Environmental hazards:	Not applicable.	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex I and the IBC Code	<b>II of Marpol</b> Not applicable.	

(Contd. on page 8)

Printing date 12.06.2020 Revision: 10.10.2018

Trade name: UltraSeal XT™ plus

(Contd. of page 7)

· UN "Model Regulation": not regulated

## 15 Regulatory information

· Chemical safety assessment:

Device is biocompatible when used as directed by dental professionals per ISO 10993-1

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H413 May cause long lasting harmful effects to aquatic life.

- · Department issuing SDS: Regulatory Affairs
- · Contact: Customer Service
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - oral - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

GB2