

Safety Data Sheet

Copyright, 2022, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 26-5784-9
 Version number:
 5.00

 Issue Date:
 20/07/2022
 Supersedes date:
 06/10/2020

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3MTM FiltekTM Supreme XTE Universal Restorative (4910, 4911, 5914, 5915)

Product Identification Numbers

I I oddet I delitilitetti	ion i tunioci s			
70-2010-7628-1	70-2010-7629-9	70-2010-7630-7	70-2010-7631-5	70-2010-7632-3
70-2010-7633-1	70-2010-7634-9	70-2010-7635-6	70-2010-7636-4	70-2010-7637-2
70-2010-7638-0	70-2010-7640-6	70-2010-7641-4	70-2010-7642-2	70-2010-7643-0
70-2010-7644-8	70-2010-7645-5	70-2010-7646-3	70-2010-7647-1	70-2010-7648-9
70-2010-7649-7	70-2010-7650-5	70-2010-7651-3	70-2010-7652-1	70-2010-7653-9
70-2010-7654-7	70-2010-7655-4	70-2010-7656-2	70-2010-7657-0	70-2010-7658-8
70-2010-7659-6	70-2010-7660-4	70-2010-7661-2	70-2010-7662-0	70-2010-7663-8
70-2010-7668-7	70-2010-7669-5	70-2010-7670-3	70-2010-7671-1	70-2010-7672-9
70-2010-7673-7	70-2010-7674-5	70-2010-7675-2	70-2010-7676-0	70-2010-7677-8
70-2010-7678-6	70-2010-7679-4	70-2010-7680-2	70-2010-7681-0	70-2010-7682-8
70-2010-7683-6	70-2010-7684-4	70-2010-7685-1	70-2010-7686-9	70-2010-7687-7
70-2010-7688-5	70-2010-7689-3	70-2010-7690-1	70-2010-7691-9	70-2010-7692-7
70-2010-7693-5	70-2010-7694-3	70-2010-7695-0	70-2010-7696-8	70-2010-7697-6
70-2010-7698-4	70-2010-7699-2	70-2010-7700-8	70-2010-7701-6	70-2010-7702-4
70-2010-7703-2				

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Restorative

Restrictions on use

For use by dental professionals only.

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113

Telephone: 136 136

E Mail: productinfo.au@mmm.com

Website: www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Skin Sensitizer: Category 1.

2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

Signal word

Warning

Symbols

Exclamation mark |

Pictograms



Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

Prevention:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280E Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention. P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents/container in accordance with applicable

local/regional/national/international regulations.

2.3. Other assigned/identified product hazards

None known.

2.4. Other hazards which do not result in classification

May be harmful if swallowed.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Silane Treated Ceramic	444758-98-9	60 - 80
(1-methylethylidene)bis[4,1-	1565-94-2	1 - 10
phenyleneoxy(2-hydroxy-3,1-propanediyl)]		
bismethacrylate		
Bisphenol A Polyethylene Glycol Diether	41637-38-1	1 - 10
Dimethacrylate (BISEMA-6)		
Diurethane Dimethacrylate (UDMA)	72869-86-4	1 - 10
Silane Treated Silica	248596-91-0	1 - 10
Silane Treated Zirconia	None	1 - 10
Polyethylene Glycol Dimethacrylate	25852-47-5	< 5
(PEGDMA)		
Triethylene glycol dimethacrylate	109-16-0	< 1
Phenyl bis(2,4,6-trimethylbenzoyl)-	162881-26-7	< 0.05
phosphine oxide		

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

SubstanceConditionCarbon monoxide.During combustion.Carbon dioxide.During combustion.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Do not get in eyes.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from oxidising agents.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Information on basic physical and chemical propertie	es
Physical state	Solid.
Specific Physical Form:	Paste
Colour	Tooth
Odour	Slight Acrylate
Odour threshold	No data available.
рН	Not applicable.
Melting point/Freezing point	No data available.
Boiling point/Initial boiling point/Boiling range	Not applicable.
Flash point	No flash point
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not classified
Flammable Limits(LEL)	Not applicable.
Flammable Limits(UEL)	Not applicable.
Vapour pressure	Not applicable.
Vapor Density and/or Relative Vapor Density	Not applicable.
Density	1.9 g/cm3
Relative density	1.9 [Ref Std:WATER=1]
Water solubility	No data available.
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	Not applicable.
Autoignition temperature	No data available.
Decomposition temperature	No data available.
Viscosity/Kinematic Viscosity	No data available.
Volatile organic compounds (VOC)	Not applicable.
Percent volatile	No data available.
VOC less H2O & exempt solvents	Not applicable.
Molecular weight	No data available.
1	ı

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

Heat.

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products

Substance

None known.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

Condition

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

Contact with the skin during product use is not expected to result in significant irritation. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >2,000 -
			=5,000 mg/kg
Silane Treated Ceramic	Dermal		LD50 estimated to be > 5,000 mg/kg
Silane Treated Ceramic	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Silane Treated Silica	Dermal		LD50 estimated to be > 5,000 mg/kg
Silane Treated Silica	Ingestion		LD50 estimated to be > 5,000 mg/kg
Diurethane Dimethacrylate (UDMA)	Dermal	Professional	LD50 estimated to be > 5,000 mg/kg
		judgement	
Bisphenol A Polyethylene Glycol	Dermal	Rat	LD50 > 2,000 mg/kg
Diether Dimethacrylate (BISEMA-6)			
Bisphenol A Polyethylene Glycol	Ingestion	Rat	LD50 > 35,000 mg/kg
Diether Dimethacrylate (BISEMA-6)			
Diurethane Dimethacrylate (UDMA)	Ingestion	Rat	LD50 > 5,000 mg/kg
(1-methylethylidene)bis[4,1-	Dermal	Professional	LD50 estimated to be > 5,000 mg/kg

phenyleneoxy(2-hydroxy-3,1- propanediyl)] bismethacrylate		judgement	
(1-methylethylidene)bis[4,1- phenyleneoxy(2-hydroxy-3,1- propanediyl)] bismethacrylate	Ingestion	Rat	LD50 > 11,700 mg/kg
Silane Treated Zirconia	Dermal		LD50 estimated to be > 5,000 mg/kg
Silane Treated Zirconia	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Polyethylene Glycol Dimethacrylate (PEGDMA)	Dermal	Rabbit	LD50 15,500 mg/kg
Polyethylene Glycol Dimethacrylate (PEGDMA)	Ingestion	Rat	LD50 9,400 mg/kg
Triethylene glycol dimethacrylate	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Triethylene glycol dimethacrylate	Ingestion	Rat	LD50 10,837 mg/kg
Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide	Dermal	Rat	LD50 > 2,000 mg/kg
Phenyl bis(2,4,6-trimethylbenzoyl)- phosphine oxide	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Silane Treated Ceramic	similar compounds	No significant irritation
Silane Treated Silica	Professional judgement	No significant irritation
Bisphenol A Polyethylene Glycol Diether	Rabbit	Minimal irritation
Dimethacrylate (BISEMA-6)		
(1-methylethylidene)bis[4,1-phenyleneoxy(2-	Rabbit	No significant irritation
hydroxy-3,1-propanediyl)] bismethacrylate		
Silane Treated Zirconia	Rabbit	No significant irritation
Polyethylene Glycol Dimethacrylate (PEGDMA)	Rabbit	Mild irritant
Triethylene glycol dimethacrylate	Guinea pig	Mild irritant
Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Silane Treated Ceramic	similar compounds	Mild irritant
Silane Treated Silica	Professional judgement	No significant irritation
Bisphenol A Polyethylene Glycol Diether	Rabbit	No significant irritation
Dimethacrylate (BISEMA-6)		
(1-methylethylidene)bis[4,1-phenyleneoxy(2-	In vitro data	No significant irritation
hydroxy-3,1-propanediyl)] bismethacrylate		
Silane Treated Zirconia	Rabbit	Mild irritant
Polyethylene Glycol Dimethacrylate (PEGDMA)	Rabbit	Moderate irritant
Triethylene glycol dimethacrylate	Professional judgement	Moderate irritant
Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value	
Silane Treated Ceramic	similar compounds	Not classified	
Bisphenol A Polyethylene Glycol Diether	Guinea pig	Not classified	
Dimethacrylate (BISEMA-6)			
Diurethane Dimethacrylate (UDMA)	Guinea pig	Sensitising	
(1-methylethylidene)bis[4,1-phenyleneoxy(2-	Mouse	Not classified	
hydroxy-3,1-propanediyl)] bismethacrylate			
Polyethylene Glycol Dimethacrylate (PEGDMA)	Guinea pig	Not classified	·

3M™ Filtek™ Supreme XTE Universal Restorative (4910, 4911, 5914, 5915)

Triethylene glycol dimethacrylate	Human and animal	Sensitising
Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	Guinea pig	Sensitising

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (BISEMA-6)	In Vitro	Not mutagenic
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	In Vitro	Not mutagenic
Silane Treated Zirconia	In Vitro	Some positive data exist, but the data are not sufficient for classification
Triethylene glycol dimethacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Silane Treated Ceramic	Inhalation	similar compounds	Some positive data exist, but the data
			are not sufficient for classification
Silane Treated Zirconia	Inhalation	Multiple animal	Some positive data exist, but the data
		species	are not sufficient for classification
Triethylene glycol dimethacrylate	Dermal	Mouse	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
(1- methylethylidene)bis[4,1-phenyleneoxy(2- hydroxy-3,1- propanediyl)] bismethacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
Triethylene glycol dimethacrylate	Ingestion	Not classified for female reproduction	Mouse	NOAEL 1 mg/kg/day	1 generation
Triethylene glycol dimethacrylate	Ingestion	Not classified for male reproduction	Mouse	NOAEL 1 mg/kg/day	1 generation
Triethylene glycol dimethacrylate	Ingestion	Not classified for development	Mouse	NOAEL 1 mg/kg/day	1 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Polyethylene Glycol Dimethacrylat e (PEGDMA)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target	Value	Species	Test result	Exposure
		Organ(s)				Duration

Silane Treated	Inhalation	pulmonary	Not classified	similar	NOAEL Not	
Ceramic		fibrosis		compounds	available	
(1- methylethylid ene)bis[4,1- phenyleneoxy (2-hydroxy- 3,1- propanediyl)] bismethacryla te	Ingestion	endocrine system hematopoietic system liver heart skin gastrointestinal tract bone, teeth, nails, and/or hair immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Silane Treated Zirconia	Inhalation	pulmonary fibrosis	Not classified	Multiple animal species	NOAEL Not available	
Silane Treated Zirconia	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Triethylene glycol dimethacrylat e	Dermal	kidney and/or bladder blood	Not classified	Mouse	NOAEL 833 mg/kg/day	78 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

Interactive Effects

Not determined.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Number	Organism	Туре	Exposure	Test endpoint	Test result
Silane Treated	444758-98-9		Data not			N/A
Ceramic			available or			

			insufficient for classification			
(1- methylethylide ne)bis[4,1- phenyleneoxy(2-hydroxy-3,1- propanediyl)] bismethacrylate	1565-94-2	Common Carp	Analogous Compound	96 hours	No tox obs at lmt of water sol	>100 mg/l
(1- methylethylide ne)bis[4,1- phenyleneoxy(2-hydroxy-3,1- propanediyl)] bismethacrylate	1565-94-2	Green algae	Endpoint not reached	96 hours	EC50	>100 mg/l
(1- methylethylide ne)bis[4,1- phenyleneoxy(2-hydroxy-3,1- propanediyl)] bismethacrylate	1565-94-2	Green algae	Experimental	96 hours	EC10	1.1 mg/l
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (BISEMA-6)	41637-38-1	Activated sludge	Estimated	3 hours	EC50	>1,000 mg/l
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (BISEMA-6)	41637-38-1	Green algae	Estimated	72 hours	EL50	>100 mg/l
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (BISEMA-6)	41637-38-1	Water flea	Estimated	48 hours	EL50	>100 mg/l
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (BISEMA-6)	41637-38-1	Zebra Fish	Estimated	96 hours	LL50	>100 mg/l
Diurethane Dimethacrylate (UDMA)	72869-86-4	Green algae	Endpoint not reached	72 hours	ErC50	>100 mg/l
Diurethane Dimethacrylate (UDMA)	72869-86-4	Water flea	Experimental	48 hours	EC50	>100 mg/l
Diurethane Dimethacrylate (UDMA)	72869-86-4	Zebra Fish	Experimental	96 hours	LC50	10.1 mg/l
Diurethane Dimethacrylate (UDMA)	72869-86-4	Green algae	Endpoint not reached	72 hours	ErC10	>100 mg/l

Silane Treated Silica Silane Treated Zirconia	248596-91-0 None		Data not available or insufficient for classification Data not available or insufficient for classification			N/A N/A
Polyethylene Glycol Dimethacrylate (PEGDMA)	25852-47-5		Data not available or insufficient for classification			N/A
Triethylene glycol dimethacrylate	109-16-0	Green algae	Experimental	72 hours	EC50	>100 mg/l
Triethylene glycol dimethacrylate	109-16-0	Zebra Fish	Experimental	96 hours	LC50	16.4 mg/l
Triethylene glycol dimethacrylate	109-16-0	Green algae	Experimental	72 hours	NOEC	18.6 mg/l
Triethylene glycol dimethacrylate	109-16-0	Water flea	Experimental	21 days	NOEC	32 mg/l
Phenyl bis(2,4,6- trimethylbenzo yl)-phosphine oxide	162881-26-7	Activated sludge	Experimental	3 hours	EC50	>100 mg/l
Phenyl bis(2,4,6- trimethylbenzo yl)-phosphine oxide	162881-26-7	Green algae	Experimental	72 hours	EC50	>100 mg/l
Phenyl bis(2,4,6- trimethylbenzo yl)-phosphine oxide	162881-26-7	Zebra Fish	Experimental	96 hours	LC50	>100 mg/l
Phenyl bis(2,4,6- trimethylbenzo yl)-phosphine oxide	162881-26-7	Green algae	Experimental	72 hours	NOEC	>100 mg/l

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Silane Treated Ceramic	444758-98-9	Data not available-insufficient	N/A	N/A	N/A	N/A
(1- methylethylide ne)bis[4,1- phenyleneoxy(1565-94-2	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	29 days (t 1/2)	

2-hydroxy-3,1- propanediyl)]						
bismethacrylate (1- methylethylide ne)bis[4,1- phenyleneoxy(2-hydroxy-3,1- propanediyl)] bismethacrylate	1565-94-2	Experimental Biodegradation	28 days	BOD	21 %BOD/ThB OD	similar to OECD 301F
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (BISEMA-6)	41637-38-1	Experimental Biodegradation	28 days	Percent degraded	24 % degraded	Non-standard method
Diurethane Dimethacrylate (UDMA)	72869-86-4	Experimental Biodegradation	28 days	CO2 evolution	22 %CO2 evolution/THC O2 evolution (does not pass 10-day window)	OECD 301B - Modified sturm or CO2
Silane Treated Silica	248596-91-0	Data not available- insufficient	N/A	N/A	N/A	N/A
Silane Treated Zirconia	None	Data not available-insufficient	N/A	N/A	N/A	N/A
Polyethylene Glycol Dimethacrylate (PEGDMA)	25852-47-5	Data not available- insufficient	N/A	N/A	N/A	N/A
Triethylene glycol dimethacrylate	109-16-0	Experimental Biodegradation	28 days	CO2 evolution	85 % weight	OECD 301B - Modified sturm or CO2
Phenyl bis(2,4,6- trimethylbenzo yl)-phosphine oxide	162881-26-7	Experimental Biodegradation	28 days	CO2 evolution	1 % weight	OECD 301B - Modified sturm or CO2

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Silane Treated	444758-98-9	Data not	N/A	N/A	N/A	N/A
Ceramic		available or				
		insufficient for				
		classification				
(1-	1565-94-2	Experimental		Log Kow	4.63	
methylethylide		Bioconcentrati				
ne)bis[4,1-		on				
phenyleneoxy(
2-hydroxy-3,1-						
propanediyl)]						
bismethacrylate						
Bisphenol A	41637-38-1	Estimated		Bioaccumulatio	6.6	Non-standard method

Polyethylene		Bioconcentrati		n factor		
Glycol Diether		on				
Dimethacrylate						
(BISEMA-6)						
Diurethane	72869-86-4	Experimental		Log Kow	3.39	Non-standard method
Dimethacrylate		Bioconcentrati				
(UDMA)		on				
Silane Treated	248596-91-0	Data not	N/A	N/A	N/A	N/A
Silica		available or				
		insufficient for				
		classification				
Silane Treated	None	Data not	N/A	N/A	N/A	N/A
Zirconia		available or				
		insufficient for				
		classification				
Polyethylene	25852-47-5	Data not	N/A	N/A	N/A	N/A
Glycol		available or				
Dimethacrylate		insufficient for				
(PEGDMA)		classification				
Triethylene	109-16-0	Experimental		Log Kow	2.3	Non-standard method
glycol		Bioconcentrati				
dimethacrylate		on				
Phenyl	162881-26-7	Experimental	28 days	Bioaccumulatio	<5	OECD 305E -
bis(2,4,6-		BCF - Carp		n factor		Bioaccumulation flow-
trimethylbenzo						through fish test
yl)-phosphine						
oxide						

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

SECTION 14: Transport Information

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable.

Hazchem Code: Not applicable

IERG: Not applicable.

International Air Transport Association (IATA) - Air Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.
Sub Risk: Not applicable.
Packing Group: Not applicable.
Marine Pollutant: Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

This product is regulated by the Therapeutics Goods Administration and is exempt from compliance with the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

SECTION 16: Other information

Revision information:

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au