

## **Safety Data Sheet**

Copyright, 2022, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 05-6733-9
 Version number:
 7.00

 Issue Date:
 07/02/2022
 Supersedes date:
 24/06/2019

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

## **IDENTIFICATION:**

### 1.1. Product identifier

RelyX<sup>™</sup> Luting (Vitremer<sup>™</sup> Luting Cement Intro Kit) (3505, 3515)

#### **Product Identification Numbers**

70-2010-2697-1

#### 1.2. Recommended use and restrictions on use

## Recommended use

Dental Product, Dental luting cement.

For use only by dental professionals.

### 1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113

**Telephone:** 136 136

E Mail: productinfo.au@mmm.com

Website: www.3m.com.au

## 1.4. Emergency telephone number

Company Emergency Hotline: EMERGENCY: 1800 097 146 (Australia only)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the SDSs for components of this product are:

05-6730-5, 05-6732-1

One or more components of this KIT is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

## TRANSPORT INFORMATION

This KIT and its components are NOT classified as Dangerous Goods.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au



## Safety Data Sheet

Copyright, 2022, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 05-6732-1
 Version number:
 7.00

 Issue Date:
 07/02/2022
 Supersedes date:
 24/06/2019

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

## **SECTION 1: Identification**

### 1.1. Product identifier

3M<sup>TM</sup> RelyX<sup>TM</sup> Luting Cement Powder (3505P, 3515P)

#### 1.2. Recommended use and restrictions on use

#### Recommended use

Dental Product, Luting cement powder

### Restrictions on use

For use by dental professionals only.

### 1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113

**Telephone:** 136 136

E Mail: productinfo.au@mmm.com

Website: www.3m.com.au

## 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

## **SECTION 2: Hazard identification**

This product is NOT classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

## 2.1. Classification of the substance or mixture

Not applicable.

### 2.2. Label elements

### Signal word

Not applicable.

**Symbols** 

## 3M<sup>TM</sup> RelyX<sup>TM</sup> Luting Cement Powder (3505P, 3515P)

Not applicable.

### **Pictograms**

Not applicable

### 2.3. Other assigned/identified product hazards

None known.

### 2.4. Other hazards which do not result in classification

May be harmful if swallowed.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Weight	
Silane Treated Glass	None	90 - 99	
Silane Treated Titanium Dioxide	404362-17-0	< 1	

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

## Eve contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### **Hazardous Decomposition or By-Products**

**Substance** 

Condition Carbon monoxide.

Carbon dioxide.

During combustion. During combustion.

## 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not get in eyes. Use personal protective equipment (eg. gloves, respirators...) as required. A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove.

### 7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

# **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

### Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use in a well-ventilated area.

### 8.2.2. Personal protective equipment (PPE)

## Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

## Skin/hand protection

See Section 7.1 for additional information on skin protection.

## **Respiratory protection**

None required.

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Information on basic physical and chemical properties				
Physical state	Solid.			
Specific Physical Form:	Coarse Powder			
Colour	White			
Odour	Slight Odour, Characteristic Odour			
Odour threshold	No data available.			
рН	Not applicable.			
Melting point/Freezing point	No data available.			
Boiling point/Initial boiling point/Boiling range	Not applicable.			
Flash point	No flash point			
Evaporation rate	Not applicable.			
Flammability (solid, gas)	Not classified			
Flammable Limits(LEL)	Not applicable.			
Flammable Limits(UEL)	Not applicable.			
Vapour pressure	Not applicable.			
Vapor Density and/or Relative Vapor Density	Not applicable.			
Density	2.8 g/cm3			
Relative density	2.8 [Ref Std:WATER=1]			
Water solubility	Not applicable.			
Solubility- non-water	No data available.			
Partition coefficient: n-octanol/water	Not applicable.			
Autoignition temperature	No data available.			
Decomposition temperature	No data available.			
Viscosity/Kinematic Viscosity	Not applicable.			
Volatile organic compounds (VOC)	Not applicable.			
Percent volatile	Not applicable.			
VOC less H2O & exempt solvents	Not applicable.			
Molecular weight	No data available.			
1				

## Nanoparticles

This material contains nanoparticles.

# **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

This material is considered to be non reactive under normal use conditions

## 10.2 Chemical stability

Stable.

### 10.3. Conditions to avoid

None known.

## 10.4. Possibility of hazardous reactions

\_\_\_\_\_

## 3M<sup>TM</sup> RelyX<sup>TM</sup> Luting Cement Powder (3505P, 3515P)

Hazardous polymerisation will not occur.

## 10.5 Incompatible materials

None known.

### 10.6 Hazardous decomposition products

**Substance** 

Condition

None known.

## **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

## 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

## Skin contact

Mechanical skin irritation: Signs/symptoms may include abrasion, redness, pain, and itching. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

### **Eve contact**

Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion.

## Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

## **Additional Health Effects:**

#### Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

## **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

### **Acute Toxicity**

Name	Route	Species	Value	
Overall product	Ingestion		No data available; calculated ATE >2,000	
_			≤5,000 mg/kg	
Silane Treated Glass	Dermal		LD50 estimated to be > 5,000 mg/kg	
Silane Treated Glass	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg	
Silane Treated Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg	

## 3M<sup>TM</sup> RelyX<sup>TM</sup> Luting Cement Powder (3505P, 3515P)

Silane Treated Titanium Dioxide	Inhalation-Dust/Mist	Rat	LC50 > 6.82 mg/l
	(4 hours)		
Silane Treated Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
Silane Treated Glass	Professional judgement	No significant irritation
Silane Treated Titanium Dioxide	Rabbit	No significant irritation

Serious Eve Damage/Irritation

Name	Species	Value
Silane Treated Glass	Professional judgement	No significant irritation
Silane Treated Titanium Dioxide	Rabbit	No significant irritation

#### **Skin Sensitisation**

Name	Species	Value
Silane Treated Titanium Dioxide	Human and animal	Not classified

## **Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity** 

Name	Route	Value
Silane Treated Titanium Dioxide	In Vitro	Not mutagenic
Silane Treated Titanium Dioxide	In vivo	Not mutagenic

Carcinogenicity

cui em ogeniery						
Name	Route	Species	Value			
Silane Treated Titanium Dioxide	Ingestion	Multiple animal	Not carcinogenic			
		species				
Silane Treated Titanium Dioxide	Inhalation	Rat	Carcinogenic.			

## Reproductive Toxicity

## Reproductive and/or Developmental Effects

For the component/components, either no data are currently available or the data are not sufficient for classification.

## Target Organ(s)

## **Specific Target Organ Toxicity - single exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target	Value	Species	Test result	Exposure
		Organ(s)				Duration
Silane Treated	Inhalation	respiratory	Some positive	Rat	LOAEL 0.01	2 years
Titanium		system	data exist, but the		mg/l	
Dioxide			data are not			
			sufficient for			
			classification			
Silane Treated	Inhalation	pulmonary	Not classified	Human	NOAEL Not	occupational
Titanium		fibrosis			available	exposure

Dagge 6 of 10

D: :1			
I Dioxide			
DIOMIGE			

### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

### **Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

#### **Interactive Effects**

Not determined.

# **SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

### 12.1. Toxicity

### Acute aquatic hazard:

Not acutely toxic to aquatic life by GHS criteria.

## Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Number	Organism	Туре	Exposure	Test endpoint	Test result
Silane Treated	None		Data not			N/A
Glass			available or			
			insufficient for			
			classification			
Silane Treated	404362-17-0		Data not			N/A
Titanium			available or			
Dioxide			insufficient for			
			classification			

## 12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Silane Treated	None	Data not			N/A	
Glass		available-				
		insufficient				
Silane Treated	404362-17-0	Data not			N/A	
Titanium		available-				
Dioxide		insufficient				

## 12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Silane Treated	None	Data not	N/A	N/A	N/A	N/A
Glass		available or				
		insufficient for				

		classification				
Silane Treated	404362-17-0	Data not	N/A	N/A	N/A	N/A
Titanium		available or				
Dioxide		insufficient for				
		classification				

### 12.4. Mobility in soil

Please contact manufacturer for more details

### 12.5 Other adverse effects

No information available.

# **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes.

# **SECTION 14: Transport Information**

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable.

Hazchem Code: Not applicable

IERG: Not applicable.

International Air Transport Association (IATA) - Air Transport

UN No.: Not applicable.

**Proper shipping name:** Not applicable.

Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.
Sub Risk: Not applicable.
Packing Group: Not applicable.
Marine Pollutant: Not applicable.

# **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **Australian Inventory Status:**

This product is regulated by the Therapeutics Goods Administration and is exempt from compliance with the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

# **SECTION 16: Other information**

#### **Revision information:**

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au



## Safety Data Sheet

Copyright, 2022, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 05-6730-5
 Version number:
 7.00

 Issue Date:
 07/02/2022
 Supersedes date:
 24/06/2019

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

## **SECTION 1: Identification**

## 1.1. Product identifier

3M<sup>TM</sup> RelyX<sup>TM</sup> Luting Cement Liquid (3505L, 3515L)

#### 1.2. Recommended use and restrictions on use

#### Recommended use

Dental Product, Cement

#### Restrictions on use

For use by dental professionals only.

### 1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113

**Telephone:** 136 136

E Mail: productinfo.au@mmm.com

Website: www.3m.com.au

## 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

## **SECTION 2: Hazard identification**

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

## 2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2.

Skin Sensitizer: Category 1.

## 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

## Signal word

Warning

## **Symbols**

Exclamation mark

### **Pictograms**



#### Hazard statements

H319 Causes serious eve irritation. May cause an allergic skin reaction. H317

## **Precautionary statements**

**Prevention:** 

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling. P264

Contaminated work clothing should not be allowed out of the workplace. P272

Wear protective gloves. P280E

**Response:** 

P302 + P352IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact P305 + P351 + P338

lenses, if present and easy to do. Continue rinsing.

If skin irritation or rash occurs: Get medical advice/attention. P333 + P313

P337 + P313IF eye irritation persists: Get medical advice/attention. P362 + P364Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents/container in accordance with applicable

local/regional/national/international regulations.

### 2.3. Other assigned/identified product hazards

None known.

## 2.4. Other hazards which do not result in classification

None known.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Copolymer of Acrylic and Itaconic Acids	25948-33-8	30 - 40
Water	7732-18-5	30 - 40
2-Hydroxyethyl Methacrylate (HEMA)	868-77-9	25 - 35
Ethyl Acetate	141-78-6	< 2

## **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

#### **Hazardous Decomposition or By-Products**

**Substance** 

Carbon monoxide.

Carbon dioxide.

**Condition** 

During combustion.

During combustion.

## 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Do not get in eyes.

## 7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

# **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Ethyl Acetate	141-78-6	ACGIH	TWA:400 ppm	
Ethyl Acetate	141-78-6	Australia OELs	TWA(8 hours):720	
			mg/m3(200 ppm);STEL(15	
			minutes):1440 mg/m3(400	
			ppm)	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

Australia OELs: Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

## 8.2. Exposure controls

## 8.2.1. Engineering controls

Use in a well-ventilated area.

### 8.2.2. Personal protective equipment (PPE)

## Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

## Skin/hand protection

See Section 7.1 for additional information on skin protection.

#### Respiratory protection

None required.

## **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Liquid.
Colour	Transparent Yellow
Odour	Slight Odour, Sweet Odour
Odour threshold	No data available.
pH	2.2 - 3.2
Melting point/Freezing point	Not applicable.
Boiling point/Initial boiling point/Boiling range	No data available.
Flash point	104 °C [Test Method: Tagliabue closed cup]
Evaporation rate	No data available.
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	Not applicable.
Flammable Limits(UEL)	Not applicable.
Vapour pressure	<=110,316.1 Pa [@ 55 °C ]
Vapor Density and/or Relative Vapor Density	No data available.
Density	1.2 g/ml
Relative density	1.2 [Ref Std:WATER=1]
Water solubility	Complete
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	Not applicable.
Autoignition temperature	No data available.
Decomposition temperature	No data available.
Viscosity/Kinematic Viscosity	175 - 225 mm <sup>2</sup> /sec
Volatile organic compounds (VOC)	No data available.
Percent volatile	No data available.
VOC less H2O & exempt solvents	No data available.
Molecular weight	No data available.

## **Nanoparticles**

This material does not contain nanoparticles.

# **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

This material is considered to be non reactive under normal use conditions

## 10.2 Chemical stability

Stable.

### 10.3. Conditions to avoid

None known.

## 10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

## 10.5 Incompatible materials

None known.

## 10.6 Hazardous decomposition products

<u>Substance</u> <u>Condition</u>

None known.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

#### 11.1 Information on Toxicological effects

## Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### Skin contact

Contact with the skin during product use is not expected to result in significant irritation. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eve contact

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### **Ingestion**

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Copolymer of Acrylic and Itaconic Acids	Ingestion	Rat	LD50 > 5,000 mg/kg
Copolymer of Acrylic and Itaconic Acids	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg
2-Hydroxyethyl Methacrylate (HEMA)	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-Hydroxyethyl Methacrylate (HEMA)	Ingestion	Rat	LD50 5,564 mg/kg
Ethyl Acetate	Dermal	Rabbit	LD50 > 18,000 mg/kg
Ethyl Acetate	Inhalation-Vapour (4 hours)	Rat	LC50 70.5 mg/l
Ethyl Acetate	Ingestion	Rat	LD50 5,620 mg/kg

ATE = acute toxicity estimate

## Skin Corrosion/Irritation

Name Species Value				
	Species	, unuc		
2-Hydroxyethyl Methacrylate (HEMA)	Rabbit	Minimal irritation		

\_\_\_\_\_

Ethyl Acetate	Rabbit	Minimal irritation
---------------	--------	--------------------

Serious Eye Damage/Irritation

Name	Species	Value
2-Hydroxyethyl Methacrylate (HEMA)	Rabbit	Moderate irritant
Ethyl Acetate	Rabbit	Mild irritant

### **Skin Sensitisation**

Name	Species	Value
2-Hydroxyethyl Methacrylate (HEMA)	Human and animal	Sensitising
Ethyl Acetate	Guinea pig	Not classified

## **Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity** 

Name	Route	Value
2-Hydroxyethyl Methacrylate (HEMA)	In vivo	Not mutagenic
2-Hydroxyethyl Methacrylate (HEMA)	In Vitro	Some positive data exist, but the data are not sufficient for classification
Ethyl Acetate	In Vitro	Not mutagenic
Ethyl Acetate	In vivo	Not mutagenic

## Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

## **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
2-Hydroxyethyl	Ingestion	Not classified for	Rat	NOAEL	premating & during
Methacrylate		female reproduction		1,000	gestation
(HEMA)				mg/kg/day	
2-Hydroxyethyl	Ingestion	Not classified for	Rat	NOAEL	49 days
Methacrylate		male reproduction		1,000	
(HEMA)				mg/kg/day	
2-Hydroxyethyl	Ingestion	Not classified for	Rat	NOAEL	premating & during
Methacrylate		development		1,000	gestation
(HEMA)				mg/kg/day	

## Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Copolymer of Acrylic and Itaconic Acids	Ingestion	nervous system	Not classified	Rat	NOAEL 5,000 mg/kg	
Ethyl Acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Ethyl Acetate	Inhalation	respiratory irritation	Some positive data exist, but the	Human	NOAEL Not available	

			data are not sufficient for classification			
Ethyl	Ingestion	central nervous	May cause	Human	NOAEL Not	
Acetate		system	drowsiness or		available	
		depression	dizziness			

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Copolymer of Acrylic and Itaconic Acids	Ingestion	endocrine system   hematopoietic system   liver	Not classified	Rat	NOAEL 200 mg/kg/day	28 days
Copolymer of Acrylic and Itaconic Acids	Ingestion	heart   bone, teeth, nails, and/or hair   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system	Not classified	Rat	NOAEL 2,000 mg/kg/day	28 days
Ethyl Acetate	Inhalation	endocrine system   liver   nervous system	Not classified	Rat	NOAEL 0.043 mg/l	90 days
Ethyl Acetate	Inhalation	hematopoietic system	Not classified	Rabbit	LOAEL 16 mg/l	40 days
Ethyl Acetate	Ingestion	hematopoietic system   liver   kidney and/or bladder	Not classified	Rat	NOAEL 3,600 mg/kg/day	90 days

## **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

## **Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

## **Interactive Effects**

Not determined.

# **SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

### 12.1. Toxicity

## Acute aquatic hazard:

Not acutely toxic to aquatic life by GHS criteria.

## Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Copolymer of Acrylic and Itaconic Acids	25948-33-8		Data not available or insufficient for classification			N/A
Hydroxyethyl Methacrylate (HEMA)	868-77-9	Turbot	Analogous Compound	96 hours	LC50	833 mg/l
2- Hydroxyethyl Methacrylate (HEMA)	868-77-9	Fathead minnow	Experimental	96 hours	LC50	227 mg/l
2- Hydroxyethyl Methacrylate (HEMA)	868-77-9	Green algae	Experimental	72 hours	EC50	710 mg/l
2- Hydroxyethyl Methacrylate (HEMA)	868-77-9	Water flea	Experimental	48 hours	EC50	380 mg/l
	868-77-9	Green Algae	Experimental	72 hours	NOEC	160 mg/l
2- Hydroxyethyl Methacrylate (HEMA)	868-77-9	Water flea	Experimental	21 days	NOEC	24.1 mg/l
	868-77-9		Experimental	16 hours	EC0	>3,000 mg/l
2- Hydroxyethyl Methacrylate (HEMA)	868-77-9		Experimental	18 hours	LD50	<98 mg per kg of bodyweight
Ethyl Acetate	141-78-6	Bacteria	Experimental	18 hours	EC10	2,900 mg/l
Ethyl Acetate	141-78-6	Crustacea	Experimental	48 hours	EC50	165 mg/l
Ethyl Acetate	141-78-6	Fish	Experimental	96 hours	LC50	212.5 mg/l
Ethyl Acetate	141-78-6	Green Algae	Experimental	72 hours	NOEC	100 mg/l
Ethyl Acetate	141-78-6	Water flea	Experimental	21 days	NOEC	2.4 mg/l

# 12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Copolymer of	25948-33-8	Data not			N/A	
Acrylic and		available-				
Itaconic Acids		insufficient				
2-	868-77-9	Experimental		Hydrolytic	10.9 days (t	OECD 111 Hydrolysis
Hydroxyethyl		Hydrolysis		half-life (pH	1/2)	func of pH

Methacrylate (HEMA)				10)		
2- Hydroxyethyl Methacrylate (HEMA)	868-77-9	Experimental Biodegradation	28 days	BOD	1	OECD 301D - Closed bottle test
Ethyl Acetate	141-78-6	Experimental Photolysis		Photolytic half- life (in air)	20.0 days (t 1/2)	Non-standard method
Ethyl Acetate	141-78-6	Experimental Biodegradation	14 days			OECD 301C - MITI test (I)

## 12.3: Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Copolymer of	25948-33-8	Data not	N/A	N/A	N/A	N/A
Acrylic and		available or				
Itaconic Acids		insufficient for				
		classification				
2-	868-77-9	Experimental		Log Kow	0.42	OECD 107 log Kow
Hydroxyethyl		Bioconcentrati				shke flsk mtd
Methacrylate		on				
(HEMA)						
Ethyl Acetate	141-78-6	Experimental		Log Kow	0.68	Non-standard method
,		Bioconcentrati				
		on				

## 12.4. Mobility in soil

Please contact manufacturer for more details

### 12.5 Other adverse effects

No information available.

# **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

# **SECTION 14: Transport Information**

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

**UN No.:** Not applicable.

**Proper shipping name:** Not applicable.

Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable.

Hazchem Code: Not applicable

**IERG:** Not applicable.

International Air Transport Association (IATA) - Air Transport

## 3M<sup>TM</sup> RelyX<sup>TM</sup> Luting Cement Liquid (3505L, 3515L)

UN No.: Not applicable.

**Proper shipping name:** Not applicable.

Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

**UN No.:** Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Marine Pollutant: Not applicable.

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **Australian Inventory Status:**

This product is regulated by the Therapeutics Goods Administration and is exempt from compliance with the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

## **SECTION 16: Other information**

#### **Revision information:**

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au